



## COMPATIBLE LOADERS FOR PRO CUTTER MODEL 1160

MANUFACTURE	LOADER TYPE	MODEL NO.	RATED OPERATING CAPACITY (LBS)	HIGH FLOW HYDRAULIC CAPACITY (GAL/MIN)	HYDRAULIC SYSTEM PRESSURE (PSI)	REMOTE ELEC. CONNECTOR FOR ATTACHMENTS (REQUIRED)
BOBCAT	SKID STEER	S300	3000	37	3300	Ω
	SKID STEER	A300	3000	37	3300	Ω
	SKID STEER	S750	3200	36.5	3500	Ω
	SKID STEER	A770	3325	36.5	3500	Ω
	SKID STEER	S770	3350	36.5	3500	Ω
	SKID STEER	S850	3950	37	3500	Ω
	COMPACT TRACK	T750	Φ 3325	36.5	3500	Ω
	COMPACT TRACK	T770	(3100) ‡ 3475	36.5	3500	Ω
	COMPACT TRACK	T870	3525	37.4	3500	Ω
CASE	SKID STEER	95XT	3150	27.6	3000	MFR. OPTION
	SKID STEER	465	3000	41.8	3050	MFR. OPTION
	SKID STEER	SV300	3000	33.2	3050	MFR. OPTION
	COMPACT TRACK	440CT	3000	33.2	3050	MFR. OPTION
	COMPACT TRACK	445CT	3300	33.2	3050	MFR. OPTION
	COMPACT TRACK	450CT	3858	41.8	3050	MFR. OPTION
CATERPILLAR	SKID STEER	262C	2974	† 33	3335	MFR. OPTION
	SKID STEER	272C	3250	33	3335	MFR. OPTION
	COMPACT TRACK	279C	3200	33	3335	MFR. OPTION
	COMPACT TRACK	289C	3850	33	3335	MFR. OPTION
	COMPACT TRACK	299C	4150	33	3335	MFR. OPTION
	MULTI TERRAIN	277C	3200	33	3335	MFR. OPTION
	MULTI TERRAIN	287C	3800	33	3335	MFR. OPTION
	MULTI TERRAIN	297C	4200	33	3335	MFR. OPTION
JCB	SKID STEER	300	3000	35.7	3335	MFR. OPTION
	SKID STEER	330	3295	35.7	3335	MFR. OPTION
	COMPACT TRACK	300T	3000	35.7	3450	MFR. OPTION
	COMPACT TRACK	330T	3200	35.7	3450	MFR. OPTION
JOHN DEERE	SKID STEER	328D	3355	† 35	3450	MFR. OPTION
	SKID STEER	332D	3200	38	3450	MFR. OPTION
	COMPACT TRACK	329D	2900	33	3450	MFR. OPTION
	COMPACT TRACK	333D	3300	34	3450	MFR. OPTION
TAKEUCHI	COMPACT TRACK	TL12	3263	† 40	3046	MFR. STANDARD
	COMPACT TRACK	TL250	2900	† 40	3000	MFR. STANDARD
TEREX / ASV	SKID STEER	TSV80	3000	42	3335	MFR. STANDARD
	COMPACT TRACK	PT80	3100	30	3000	MFR. STANDARD
	COMPACT TRACK	PT100	4000	ADJ. 30-45	3800	MFR. STANDARD

† OPTIONAL REAR COUNTER WEIGHT KIT REQUIRED

Φ BOBCAT TRACK LOADER WITH "ROLLER SUSPENSION OPTION" NOT ALLOWED.

‡ BOBCAT TRACK LOADER WITH "ROLLER SUSPENSION OPTION".

Ω BOBCAT REMOTE ELEC. CONTROL CONNECTION CAN NOT BE USED. MUST USE PRO CUTTER UNIVERSAL ELEC. CONTROL KIT.